






15EDGKNHB/BG/HBM-3.5


- 双排插头PUSH-IN接线。
- 小体积，高密度。
- 带释放杆挂钩，无需任何工具实现对锁和释放。
- 提供配套的直针、弯针、带法兰、闭口的结构。
- Double-row male and female, PUSH-IN wiring.
- Small size, high density.
- With release hook, free tool to realize to lock and release.
- Providing the mating straight type, angle type, flange type and closed type.




15EDGKNHB-3.5



15EDGKNHBM-3.5



15EDGRHD-3.5



15EDGRHDM-3.5

技术参数 Technical data

APPROVAL: CE cULus

型号 Model	线径 Wire range	线数 Poles	IEC61994技术参数 (IEC61984 data sheet)		UL1059技术参数 (UL1059 data sheet)	
			电压(V) Rated voltage	电流(A) Rated current	电压(V) Rated voltage	电流(A) Rated current
15EDGKNHB-3.5	28-16/0.2-2.5AWG/mm ²	04-48P	320	13.5	300	10
15EDGKNHBG-3.5	28-16/0.2-2.5AWG/mm ²	04-48P	320	13.5	300	10
15EDGKNHBM-3.5	28-16/0.2-2.5AWG/mm ²	04-48P	320	13.5	300	10
15EDGRHD-3.5	—	04-48P	320	13.5	300	10
15EDGRHDM-3.5	—	04-48P	320	13.5	300	10

应用行业 Application

工业自动化、新能源、电梯、电力电气、电源、轨道交通、机械等行业。
Industrial automation, new energy, elevator, electric power, power supply, machinery.



产品包装方式 Packing

Product model	Pcs./Pkt.	Product model	Pcs./Pkt.
15EDGKNHB-3.5-04P	50	15EDGKNHB-3.5-16P	50
15EDGKNHB-3.5-06P	50	15EDGKNHB-3.5-18P	50
15EDGKNHB-3.5-08P	50	15EDGKNHB-3.5-20P	50
15EDGKNHB-3.5-10P	50	15EDGKNHB-3.5-22P	50
15EDGKNHB-3.5-12P	50	15EDGKNHB-3.5-24P	50
15EDGKNHB-3.5-14P	50		

型号对照 Cross reference

DEGSON	同行1/Competitor1	同行2/Competitor2
15EDGKNHB/G/M	B2CF3.50	-
15EDGRHD/M	SZL3.50	-

产品订货 How to order

15EDGKNHB-3.5 — 0 4 P — 1 4 — 0 0 A(H) Standard

Series NO. NO. of pole

1 Single pitch
2 Double pitch

通用色 General Color
4 Green PANTONE 556C
DEGSON 04